



Approval Marks



Certified

EN 61347-1:2008
 EN 61347-2-13:2006
 EN 62384:2006

Electronic

Parameter	Conditions	Min	Nom	Max	Unit
I/P Voltage Range		90	230	264	Vac
Input Frequency		47	50-60	63	Hz
Output Power(Pout)	350mA LED	6	-	12	W
Input Current(Iin)	25°C,Nominal Input@230VAC	-	70	-	mA
Output Voltage(Vout)		18	-	36	Vdc
Output Current(Iout)	25°C,Nominal Input	315	350	385	mA
Power Factor	Full Load	-	0.95	-	
Protection	Overload Protection				
	Short Circuit Protection				
	Over Heat Protection				
Ambient Temp.		-20	-	+50	°C
Case Temp. (Tc)	Normal Conditions	-	-	+75	°C


Lamp Type High Power LED 1.2W x 6~10

Application Space

Indoor Use
 (Low Humidity, No Condensation)

Physical

Parameter



- L : 235 mm H : 21 mm
- M : 218.5 mm K :
- N : R : 1.3 mm
- W : 29.5 mm Slot On One Side Allowing Alignment : M+/-3 mm
- Tolerance : $\geq 0 \sim 100 \geq \pm 0.5\text{mm}$
 $100 \geq \pm 1 \text{ mm}$
- Terminal Block : PRI : Push Button
 SEC : Push Button and Quick Connect
- Housing Material : Metal, No Sharp Edges
- Soldering : Lead - Free, Comply With RoHS
- Label : Surface Print

Wiring Diagram

