

# SAGEM


## MOD170

## MOD190



## *GPRS Modem for industrial applications, telemetry, security systems and industry*

*GPRS class 8 (4+1) with PBCCH support  
Voice and Data support  
Extended AT commands  
RS232 serial link  
Easy integration  
Plug and play*



*Add wireless features to your devices  
with Sagem MOD170/MOD190!*

*No matter if you do not know about wireless,  
MOD170/MOD190 will add the high speed GPRS data  
functionalities to your devices in a quick and smart way.*

*This modem constitutes a self-contained, fully integrated  
implementation of the GSM/GPRS standard.  
Thanks to standard interfaces, it can be integrated into any  
systems which offers unlimited assets.*

*Therefore your security system, telemetry, tracking system,  
vending machines will enter the wireless world in an instant...  
you will save time and money, and create a whole range of  
new services.*

*Besides with its end-user package, MOD170/MOD190 can  
be easily connected to your PC and help you browse the  
internet on the move.*



## Marketing features

- Tiny size
- Built-in enhanced functionalities
- Advanced GPRS capabilities class 8 (up to 56 kbps)
- Triple band and interoperable all over the world
- Benefit of the know-how and large production capacity of a world class mobile phone maker
- Fully Shielded and ready-to-use

## General features

- Tiny form factors: 60 x 40 x 10 mm
- Light weight: 35g
- Volume: 24 cm<sup>3</sup>
- Triple band EGSM900 / DCS1800 / PCS1900
- Class 4 (2W) for EGSM900
- Class 1 (1W) for DCS1800 / PCS1900
- Power supply 5 VDC +/- 5%
- Standby mode: 2.5mA (typ)
- ETSI GSM Phase 2+Type Approved
- FTA approved
- Data: CSD, SMS, Fax, GPRS Multi-slot class 8 (4+1), PBCCH and ciphering support, class B terminal
- Audio capabilities (only for MOD190)
- Remote control by AT commands



## Packaging


- Mounting holes for fixing
- Shock resistant package
- RF shielded package
- Operating temperature range at least -20/+55°C
- Storage temperature range at least -40/+85°C

## Interface

- MMCX antenna connector
- 60-pin connector including RS232 serial link
- Internal 3V SIM card reader
- Mounting: 2 screw holes

## Documentation

- Modem booklet
- User's guide
- List of supported AT commands (MO170/ MO190)



The MOD170/MOD190 evaluation board is optional. It can be ordered from SAGEM S.A or directly from your distributor.

SAGEM SA may, at any time and without notice, make changes or improvements to the products and services offered and/or cease producing or commercialising them. The SAGEM logo and trademark are the property of SAGEM SA. 07/2003

**SAGEM SA** Mobile Phones Division

Phone +33 1 40 70 63 63 Fax +33 1 40 70 66 40  
www.sagem.com

Head Office : Le Ponant de Paris, 27 rue Leblanc – 75512 PARIS CEDEX 15 – France  
SAGEM SA - Société anonyme à directoire et conseil de surveillance au capital de 33 300 000 € – 562 082 909 RCS PARIS

