

**LA-PE Range - Constant Current LED Drivers with PFC**



**Features:**

- Constant Current Driver
- Universal AC Input
- Built-in active PFC function (PFC>0.9)
- Re-Wireable terminal blocks for I.P & O.P.
- Protections: Short Circuit / Over Current
- Small and attractive cream case
- 2 Year Warranty

**Compliance:**

- Magnetic Emissions: EN55015
- Harmonic: EN61000-3-2
- Immunity: EN61547
- Safety: EN61347-1, EN61347-2-13



Model	Input	Output	Suggested Loading	Efficiency (full load)	Dimensions (LxWxH)
LA6PE-350	100-240Vac	3-24Vdc 350mA	1---6 LED	≥76%	89x39x23mm
LA6PE-700	100-240Vac	2-12Vdc 700mA	1---3 LED	≥70%	89x39x23mm
LA12PE-350	100-240Vac	16-36Vdc 350mA	5---10 LED	≥82%	114x45x28mm
LA12PE-700	100-240Vac	8-18Vdc 700mA	3---5 LED	≥80%	114x45x28mm
LA20PE-350	100-240Vac	30-70Vdc 350mA	9---18 LED	≥85%	140X45x28mm
LA20PE-700	100-240Vac	12-35Vdc 700mA	4---9 LED	≥82%	140X45x28mm